

Product Data Sheet



MEDAL CHROME ALUMINIUM SILVER

No	MP53
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Chrome Aluminum Silver will reflect heat and reduce the overall temperature of a home or building. This product is primarily used to protect Galvanized Iron Roofs, Steel Fencing, Posts and Gates and on other areas where a durable silvery finish is required.

PRODUCT USES:

- Metal & Galvanized Iron Surfaces.

PRODUCT BENEFITS:

- Quick Drying
- Good Adhesion Properties
- Excellent Hiding Power
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Iron & Steel: Remove oil/grease and surface rust before painting. Apply one coat of Medal Solvent Etch Primer, followed by two coats of Medal Chrome Aluminium Silver.

Galvanized Iron: Clean and remove all oil/grease with Medal Galvanized Iron Cleaner, prior to applying one coat of Medal Dual Steel Primer, followed by two coats of Medal Chrome Aluminum Silver.

Asbestos/Fibre Cement: Apply one coat of Medal Bonding Liquid, followed by two coats of Medal Chrome Aluminum Silver.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Spot prime all bare areas with the appropriate primer before applying two coats of Medal Chrome Aluminium silver.

Note: This product is suitable for spray application.

Application:

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (mohair) paint roller, and allow 30 Minutes drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in silver.

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity. Based on SABS test method.

Type	Solvent-Based
Enamel	
Finish	Silver
Drying Time @ 25°C	Touch Dry: 4 hrs Hard Dry : 16 hrs
Re-coating Time	4 hours
Viscosity	15 - 20 Sec/FC4 /25°C
Specific Gravity	0.90 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

