PRODUCT DATA SHEET MEDAL PROFESSIONAL TRADE STEEL PRIMER No PT10 Date 10/23

Professional Trade products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Professional Trade Steel Primer is an economy quick drying solvent-based primer, which is primarily used to protect steel surfaces against rust. This product has good adhesion and anti-corrosive properties.

PRODUCT USES

- Metal Surfaces.
- ☐ Ideal for steelwork such as Gates, Fencing & Burglar Bars.

PRODUCT BENEFITS

- □ Quick Drying
- □ Excellent Adhesion
- ☐ Apply with Brush or Spray
- ☐ Interior & Exterior Use
- □ Quality Guaranteed

SURFACE PREPARATION

<u>New Surfaces</u>: Surface/s must be thoroughly clean, dry and in sound condition before commencing work.

Remove all rust with a wire brush or sandpaper before applying one coat of Medal Professional Steel Primer, followed by two coats of Medal QD Enamel or Medal High Gloss Enamel paint in the desired colour.

APPLICATION

Stir the contents thoroughly before use. For spray application: Ready for use. No thinning is required. Apply this product with a paintbrush or conventional spray, and allow overnight to dry before applying the final coat/s of paint. For dipping purposes 5% thinning is required. Apply this product at 14-18 Sec/F4@25°.

Spray application: use with standard high-pressure spray guns – air pressure 3-5 bar. For any other/spray methods of application contact our technical department Clean tools (brushes, & spraying equipment) with Medal Quick Drying Thinners immediately after use.

COLOURRANGE

Available in Red Oxide and Grey.

SPREADING RATE

This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type Alkyd Finish Matt

Drying Time @ 25°C Touch Dry: 30 Minutes

Hard Dry : 4 Hour

Re-coating Time 6 Hour

Viscosity 65-75 Sec/F4/25°C
Specific Gravity 1.2 kg / litre
Storage Dry and Cool area

Pack Size 5Lt; 25Lt;

PRECAUTIONS

- Do not apply if rain is imminent.
- \blacksquare Apply at an ambient temperature of 5 to 35°C.
- ☐ Keep out of reach of children.
- Wash hands with Thinners and Hot Soapy Water immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- Wear protective clothing.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.