Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL ACRYLOSEAL 4 IN 1 PVA	No	MARS01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Acryloseal Pva is a medium quality paint, suitable for all interior and exterior surfaces. This product has excellent filling, water resistant and hiding power properties. It can be applied to a variety of surfaces where a matt finish is required.

PRODUCT RECOMENDED USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Interior & Exterior Walls.

PRODUCT BENEFITS

- Quick Drying
- Good Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use
- Lead Free
- 7 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply two coats of Medal Acryloseal Pva,

Asbestos/Fibre Cement: Apply two coat of Medal Acrlyoseal Pva.

Gypsum Plaster (Rhinolite): Apply one coat of Plasterbond followed by two coat of Medal Acryloseal Pva

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply two coats of Medal Acryloseal Pva.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white, Tint Bases and standard colours

SPREADING RATE

This product will cover approximately 6-8 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min to 1 Hour
	Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	108-120 Krebs units
Specific Gravity	1.45 kg / litre
Water Resistance	**>6 hours – No damage**
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackffiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of 7 years subject to the adherence by the purchaser to comply with the “Instructions for Use “appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.