Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL ACRYLOTEX 4 IN 1 PVA	No	MATX01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Acrylotex Four in One Pva is a good quality fine texture paint, suitable for exterior surfaces. This product is a primer and flexible topcoat all in one and has been developed with bonding properties to adhere to poor plaster surfaces, it also has excellent filling and water-resistant properties. It can be applied to a variety of surfaces where a matt fine texture finish is required.

PRODUCT RECOMMENDED USES:

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Primed Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Ideal solution for rough cast walls.
- Exterior Walls.

PRODUCT BENEFITS

- Quick Drying
- Excellent Bonding Properties
- Alkali Resistant
- Covers Hairline Cracks
- UV and Water resistant
- Good Hiding Power
- Lead Free
- 7 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.Powdery surfaces must be treated with Medal Plasterbond.

Concrete/Cement Plaster: Apply two coats of Medal Acrylotex Four in One Pva,

Asbestos/Fibre Cement: Apply two coats of Medal Acrylotex Four in One Pva.

Gypsum Plaster (Rhinolite): Apply one coat of Medal Plaster Primer followed by two coats of Medal Acrylotex Four in One Pva

Previously Painted PVA Surfaces: Thoroughly clean and prepare surfaces by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply two coats of Medal Acrylotex Four in One Pva.

Note: Not recommended for clay-based substrates.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with water immediately after use.

COLOUR RANGE

Available in lighthouse white and 9 standard colours.

SPREADING RATE

This product will cover approximately 6-8 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Fine Texture
Drying Time @ 25°C	Touch Dry: 30 Min to 1 Hour Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	130-140 Krebs units
Specific Gravity	1.45 kg / litre
Water Resistance	**>6 hours – No damage**
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if
- necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Scrubbing Brushes; Stepladder.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of 7 years subject to the adherence by the purchaser to comply with the “Instructions for Use “appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.