Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL BRICK DRESSING	No	MBDR01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Brick Dressing is an all-weather resistant finish, which is specifically designed to beautify, enhance and protect interior and exterior brick or stonework. A quick-drying product, which can be used on a variety of surfaces such as face brick, stone and quarry stone surfaces where a durable clear glossy finish is required.

PRODUCT USES

- ❑ Suitable for "Interior and Exterior" surfaces made from Brick & Stone.

PRODUCT BENEFITS

- ❑ Complete Protection
- ❑ Enhances the Natural Shades
- ❑ Easy to Clean & Maintain
- ❑ Dries to a Clear Glossy Finish
- ❑ Apply with Brush or Spray
- ❑ Interior & Exterior Use
- ❑ Lead Free
- ❑ Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before varnishing. Apply one coat thinned down with 10% Mineral Turpentine followed by two coats(unthinned) of Medal Brick Dressing to a clean and prepared surface.

Previously Varnished Surfaces: Thoroughly clean and prepare surface/s to be varnished by removing all dirt, grease, grime, wax, oil and flaking varnish. The entire surface area must be properly cleaned with clean water and allowed to dry for 24 hours before commencing work. Apply one coat thinned down with 10% Mineral Turpentine followed by two coats of Medal Brick Dressing.

Warning: This product is not suitable for use on Vinyl, Slasto or Ceramic Tiled floors, and must not be used on Damp surfaces.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or spray and allow overnight drying time between coats. For Spray Application thin down with 15% Mineral Turpentine.Clean tools (brushes & equipment) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in clear.

SPREADING RATE

This product will cover approximately 8- 10 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	Touch Dry: 4 Hours Hard Dry : 16 Hours
Re-coating Time	16 Hours
Viscosity	10 - 15 secs
Specific Gravity	0.90 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS

- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature lower than 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Mineral Turpentine immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.