Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL CHROME ALUMINIUM SILVER	No	MALU01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Chrome Aluminium Silver will reflect heat and reduce the overall temperature of a home or building. This product is primarily used to protect Galvanised Iron Roofs, Steel Fencing, Posts and Gates and on other areas where a durable silvery finish is required.

PRODUCT USES

- Metal & Galvanised Iron Surfaces.

PRODUCT BENEFITS

- Quick Drying
- Good Adhesion Properties
- Excellent Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use
- Lead Free
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting**.**

Iron & Steel: Remove oil/grease and surface rust before painting. Apply one coat of Medal Solvent Etch Primer, followed by two coats of Medal Chrome Aluminium Silver.

Galvanised Iron: Clean and remove all oil/grease with Medal Galvanised Iron Cleaner, prior to applying one coat of Medal Dual Steel Primer, followed by two coats of Medal Chrome Aluminum Silver.

Asbestos/Fibre Cement: Apply one coat of Medal Bonding Liquid, followed by two coats of Medal Chrome Aluminum Silver.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. . Light sand and apply a single coat of Medal Dual Steel primer or Medal QD Red Oxide before applying two coats of Medal Chrome Aluminium Silver.

Note: This product is also suitable for spray application.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (mohair) paint roller and allow 30 Minutes drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOURRANGE

Available in aluminium silver.

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Solvent-Based Enamel
Finish	Silver
Drying Time @ 25°C	Touch Dry: 2 hours
	Hard Dry : 4 -6 hours
Re-coating Time	4 hours
Viscosity	20 - 25 Sec/FC4 /25°C
Specific Gravity	0.90 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt, 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paint Brush & Paint Roller Trayset, Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.