Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL CONTRACTORS ACRYLIC PVA

No	MCON01
Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION
Medal Contractors Acrylic Pva is a superior quality paint, which has been developed specifically to decorate and protect all interior and exterior surfaces. This product has excellent filling and hiding power properties recommended for walls and ceilings.

PRODUCT USES
- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Ideal for Interior & Exterior Walls & Ceilings

PRODUCT BENEFITS
- Excellent Durability
- Quick Drying
- Fully Washable
- Good Hiding Power
- Soft Matt Finish
- Apply with Brush or Roller
- Interior & Exterior Use
- Lead Free
- 5 Year Guarantee

SURFACE PREPARATION
New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.
Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Contractors Acrylic Pva..
Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Contractors Acrylic Pva.
Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by two coats of Medal Contractors Acrylic Pva.
Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Contractors Acrylic Pva
Iron & Steel: Clean and remove all grease and rust. Apply one coat of Medal Dual Steel Primer followed by one coat of Medal Universal Undercoat and two coats of Medal Contractors Acrylic Pva

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond, prior to applying two coats of Medal Contractors Acrylic Pva..
Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Contractors Acrylic Pva..

APPLICATION
Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE
Available in white & standard colours.

SPREADING RATE
This product will cover approximately 7-9m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Minutes
	Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	100-110 Krebs units
Specific Gravity	1.40 kg / litre
Wash ability	>5000 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS
- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST
Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackffiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE
Medal Paints will guarantee this product for a period of 5 years subject to the adherence by the purchaser to comply with the “Instructions for Use “appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.