Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL HIGH GLOSS ENAMEL	No	MHGE01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:
Medal High Gloss Enamel is a superior quality paint suitable for decorating and protecting all interior and exterior surfaces. This product has an excellent gloss level, fully washable, and it can be applied to a variety of surfaces where a long-lasting glossy finish is required.

PRODUCT USES:
- ❑ New and previously painted surfaces made from Cement Plaster, Concrete, and Brickwork & Gypsum Plaster.
- ❑ Primed Metal & Wooden Surfaces.
- ❑ Ideal for Steel Door & Window Frames; Kitchen & Bathroom Walls; Gates; Steel Fencing; Skirting Boards and Garden Furniture etc.

PRODUCT BENEFITS:
- ❑ Excellent Durability Stain & Dirt Resistant Good Hiding Power
- ❑ Interior & Exterior Use
- ❑ Lead Free
- ❑ 7 Year Guarantee

SURFACE PREPRATION:
New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.
Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by one coat of Medal Universal Undercoat. Apply two coats of Medal High Gloss Enamel.
Galvanized Iron: Clean and remove all oil/grease prior to applying one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.
Iron & Steel: Clean and remove all grease and rust. Apply one coat of Medal Solvent Etch
primer, followed by one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.
Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Spot prime all bare areas with the correct primer, followed be one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.

APPLICATION:
Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOURRANGE
Available in white, standard colours and three different types of tint bases.

SPREADING RATE
This product will cover approximately 8-10m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	
Touch Dry:	4 hrs.
Hard Dry:	16 Hours
Re-coating Time	16 Hours
F.O.G.	<10µ
Viscosity	80-85 KU
Specific Gravity	1.10 kg / litre
Storage area	Dry and Cool
Pack Size	500ml; 1Lt; 5Lt; 20Lt

PRECAUTIONS:
Do not apply if rain is imminent.
Apply at an ambient temperature of 5 to 35°C.
Keep out of reach of children.
Wash hands with Water immediately after use.
Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:
Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE
Medal Paints will guarantee this product for a period of 7 years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.