Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL INDUSTRIAL SANDING SEALER	No	MISSE01
	Date	06/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Sanding Sealer is a silky-smooth transparent wood filler and sealer, which is used to fill any slight imperfections (open grain) in timber before a topcoat of Medal Wood Varnish is applied. A top quality quick drying product suitable for all interior woodwork such as furniture Knotty Pine Ceilings, Wood Paneling and Build-in Cupboards etc.

PRODUCT USES

- ❑ Suitable for "Interior & Exterior" surfaces.

PRODUCT BENEFITS

- ❑ Quick-drying Wood Filler & Sealer
- ❑ Apply directly over Stained Timber
- ❑ Ideal for Furniture & Cupboards
- ❑ Dries to a smooth clear silky finish
- ❑ Apply with Paintbrush or Spray
- ❑ Interior or Exterior Use
- ❑ Lead Free

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before commencing work.
Sand surface (in direction of grain) before applying one thinned coat of Medal Sanding Sealer. Sand surface to a smooth finish. Apply two coats of Medal Wood Varnish, and allow overnight drying time between coats.

Previously Varnished Surfaces: This product is not suitable for previously varnished or painted surfaces. These surfaces must be stripped back to bare wood, prior to following the "instructions for Use" for New Surfaces.

APPLICATION

Stir the contents thoroughly before use This product may be thinned down by up to 10% with Medal Lacquer Thinners for spray application. Apply one coat with a paintbrush or spray and allow one hour drying time before finishing off with 1-2 coats of Medal Wood Varnish. Clean tools (brushes & spraying equipment) with Medal Lacquer Thinners immediately after use.

COLOUR RANGE

A milky colour that dries to a satin clear finish.

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Nitro Cellulose
Finish	Satin Sheen
Drying Time @ 25°C	Touch Dry: 15 Minutes
	Hard Dry : 1 Hour
Re-coating Time	1 Hour
Viscosity	65 – 70 Sec/F4/25°C
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS

- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature of 5 to 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Thinners and Hot Soapy Water immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- ❑ Wear protective clothing.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.