Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL LOW SHEEN ACRYLIC PVA	No	MLSH01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Low Sheen Acrylic is a superior quality paint with a fine-smooth finish, which has been developed to protect and beautify all interior and exterior surfaces. This product is fully washable with excellent dirt and stain resistance. It can be applied to a variety of surfaces where a durable low-sheen finish is required.

PRODUCT USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Primed Metal & Wooden Surfaces.
- Ideal for Interior & Exterior Walls.

PRODUCT BENEFITS

- Stain & Dirt Resistant
- Fully Washable
- Good Scrub Resistance
- Excellent Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use
- Lead Free
- 12 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Low Sheen Acrylic.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Low Sheen Acrylic.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Low Sheen Acrylic.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Low Sheen Acrylic.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by two coats of Medal Low Sheen Acrylic.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Bonding Liquid, prior to applying two coats of Medal Low Sheen Acrylic. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Low Sheen Acrylic.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white and Tint bases

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic
Finish	Low -Sheen
Drying Time @ 25°C	Touch Dry: 30 Minutes
	Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	112-120 Krebs units
Specific Gravity	1.20 kg / litre
Wash ability	>10.000 Scrubs
Storage	Dry and Cool area

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of 12 years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.