Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PAVE COAT	No	MPAV01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Pave Coat is a superior quality paint, which was specifically developed to provide an exceptional hardwearing finish for concrete paving bricks. A floor coating that has excellent alkali resistance properties and provides complete protection against the weathering elements. The paint finish makes it easy to clean and maintain.

PRODUCT USES

- ❑ Suitable for Concrete Paving Bricks.

PRODUCT BENEFITS

- ❑ Durable Semi Sheen Finish
- ❑ Excellent Alkali Resistance
- ❑ Fully Washable
- ❑ Good Hiding Power
- ❑ Apply with Brush or Roller
- ❑ Exterior Use
- ❑ Lead Free
- ❑ 5 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.
Apply one coat of Medal Plasterbond, followed by two coats of Medal Pave Coat.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Remove grease and grime etc with Medal Sugar Soap mixed with water, and a stiff-bristled brush or broom. Rinse off with clean water and allow to dry. On worn areas, apply one coat of Medal Plasterbond, prior to applying two coats of Medal Pave Coat.

*Please Note: Not recommended for Driveway (Hot tyre surfaces)

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush, block brush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in standard colours.

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Pure Acrylic
Finish	Semi Sheen
Drying Time @ 25°C	Touch Dry: 30 Minutes
	Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	105 – 115 Krebs units
Specific Gravity	1.20 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature of 5 to 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Water immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Block Brush; Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Paint Scraper.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of 5 years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.