Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PREMIUM NON-DRIP ENAMEL

No	MPNDE01
Date	04/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION
Medal Premium Non-Drip Enamel is a hardwearing semi-gloss polyurethane-based "non-drip" paint, which is suitable for decorating and protecting all interior surfaces. This product is ideal for use on kitchen and bathroom walls, doors, cupboards and many other areas where a durable semi-gloss finish is required.

PRODUCT USES
- New or previously painted surfaces made from Cement Plaster; Concrete; Brickwork etc.
- Ideal for Kitchens and Bathrooms.
- Primed Metal & Wooden Surfaces.

PRODUCT BENEFITS
- Non-Drip Enamel
- Fully Washable
- Heat & Steam Resistant
- Apply with Brush or Roller
- Lead Free
- 10 Year Guarantee

SURFACE PREPARATION
New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.
Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer followed by two coats of Medal Premium Non-Drip Enamel.
Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer followed by two coats of Medal Premium Non-Drip Enamel.
Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Medal QD Steel Primer, followed by two of Medal Premium Non-Drip Enamel
Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed two coats of Medal Premium Non-Drip Enamel.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Bonding Liquid, prior to applying two coats of Medal Premium Non-Drip Enamel. Spot prime all bare areas with the correct primer and build up any uneven areas with-Medal Universal Undercoat. Apply two coats of Medal Premium Non – Drip Enamel.

APPLICATION
Do not stir or shake container before use. If stirred accidentally, leave paint to stand for 2 hours to regain its correct consistency again under ambient temperature conditions. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE
Available in white, aged bronze and tintbases

SPREADING RATE
This product will cover approximately 8-10m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Thixotropic Alkyd
Finish	Semi-Sheen
Drying Time @ 25°C	Touch Dry : 4 Hours
	Hard Dry : 16 Hours
Re-coating Time	16 Hours
Viscosity	3.0 -3.5 poise
Specific Gravity	1.25 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt , 5Lt

PRECAUTIONS
- Do not apply if rain is imminent.
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST
Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackffiller; Paint Scraper; Mineral Turpentine; Stepladder.

GUARANTEE
Medal Paints will guarantee this product for a period of 10 years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.