Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PREMIUM ONE COAT	No	MPOC01
	Date	04/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium One Coat Paint is a pure acrylic paint with a silky-smooth finish, which has been especially formulated to provide complete cover to all interior and exterior surfaces in one single application. This product is fully washable with excellent hiding power, and abrasion, dirt and stain resistant properties. It can be applied to numerous surfaces such as Cement Plastered Walls, Asbestos or Fibre Cement boards and on other areas where a durable silky-smooth finish is required.

PRODUCT USES

- ❑ New or previously painted surfaces made from Cement Plaster; Concrete; Brickwork & Gypsum Plaster.
- ❑ Ideal for Interior Walls – Lounge; Dining room Bedrooms; Study; Passages & Exterior Walls

PRODUCT BENEFITS

- ❑ Pure Acrylic Paint
- ❑ One Coat Application
- ❑ Fully Washable
- ❑ Stain & Dirt Resistant
- ❑ Apply with Brush or Furpile Roller
- ❑ Interior & Exterior Use
- ❑ Lead Free
- ❑ 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply two coats of Medal Plaster Primer, followed by one coat of Medal Premium One Coat Acrylic Paint.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by one coat of Medal Premium One Coat Paint.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Premium One Coat Acrylic Paint.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and one coat of Medal Premium One Coat Paint.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by one coat of Medal Premium One Acrylic Coat Paint.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plaster bond, and followed by one coat of Medal Premium One Coat Acrylic Paint. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by one coat of Medal Premium One Coat Paint

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply a generous, even coat of paint ensuring a wet edge is maintained at all times. Do not overspread this product as this could lead to an uneven film build that may require a second coat. Apply this product with a high-quality paintbrush or furpile paint roller. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white.

SPREADING RATE

This product will cover approximately 5m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Pure Acrylic
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Minutes
	Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	110-120 Krebs Units
Specific Gravity	1.42 kg / litre
Wash ability	>10.000 Scrubs
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt; 20Lt

PRECAUTIONS

- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature of 5 to 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Water immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- ❑ Use Medal Bonding Primer for Gypsum Plaster.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

GUARANTEE

Medal Paints will guarantee this product for a period of 10 years subject to the adherence by the purchaser to comply with the “Instructions for Use “appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.