Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PREMIUM ROOF PAINT	No	MPRP01
	Date	04/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium Roof Paint is an all-weather-resistant pure acrylic paint with a sheen finish, which has been developed to provide good durability combined with excellent dirt retention properties. This product is suitable for Asbestos Cement Roof Sheets or Tiles, Cement or Clay Roof Tiles and on primed Galvanised Iron Roofs.

PRODUCT USES

- Most types of Roofs (excluding. Slate).
- Concrete Windowsills.
- Asbestos/Fibre Cement surfaces such as Facia Boards; Garden Pots; Gutters & Downpipes.
- Primed Metal & Wooden Surfaces.

PRODUCT BENEFITS

- Pure Acrylic Paint
- Excellent UV Resistance
- Apply with Brush or Roller
- Exterior Use
- Lead Free
- 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Galvanised Steel: Clean and remove all manufacturers pre-treatment (oil/grease), prior to applying one coat of Medal Galvanised Iron and one coat Medal Dual Steel Primer, followed by two coats of Medal Premium Roof Paint.

Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Medal Galvanised Iron and one coat Medal Dual Steel Primer, followed by two coats of Medal Premium Roof Paint.

Cement Roof@ Nutec Tiles: Apply the first coat thinned with 10% water to aid penetration, followed by two coats of Medal Premium Roof Paint un-thinned.

Asbestos/Fibre Cement: Apply one coat of Medal Plasterbond, followed by two coats of Medal Premium Roof Paint.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond prior to applying two coats of Medal Premium Roof Paint applied unthinned. Ensure the surface is correctly prepared before commencing to paint.

Warning: Avoid painting if the roof is too hot or covered with mildew, which means that the recommended times to paint may vary as indicated under Application.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. . For best results, apply this product between 08,00-11,00 hrs and again from 15,00-18,00 hrs. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOURRANGE

Available in standard colours.

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity.
Nutec tiles will cover approx. 4-5 square m per litre..

TECHNICAL DATA

Type	Pure Acrylic
Finish	Sheen
Drying Time @ 25°C	Touch Dry: 1 Hour
	Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	110-120 Krebs Units
Specific Gravity	1.26 kg / litre
Wash ability	>10.000 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Block Brush; Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Stepladder.

GUARANTEE

Medal Paints will guarantee this product for a period of 10 years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.