Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PEMIUM TEXTURED PAINT	No	MPTX01
	Date	04/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium Texture Acrylic is a hard wearing exterior wall coating, which is recommended for use on exterior concrete and cement-plastered surfaces. This product has good flexibility and tensile strength. It covers all hairline cracks, and it has excellent alkali and water-resistant properties. Also suitable on areas where a fine durable matt textured finish is required.

PRODUCT USES

- New or previously painted surfaces made from Cement Plaster; Concrete; Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Boards.
- Primed Metal Surfaces.
- Ideal for Exterior Walls.

PRODUCT BENEFIT

- Hides Hairline Cracks
- Excellent UV Resistance
- Apply with Brush or Roller
- Ideal for Exterior Surfaces
- Lead Free
- 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal PremiumTexture Acrylic.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Premium Texture Acrylic.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by two coats of Medal PremiumTexture Acrylic.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Premium Texture Acrylic.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by two coats of Medal Premium Texture Acrylic.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond prior to applying two coats of Medal Premium Texture Coat.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or lambswool paint roller, and allow +/- 6 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in Std colours and Tintbaes

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Minutes
	Hard Dry : 6 Hours
Re-coating Time	6 Hours
Viscosity	125 -135 Krebs Units
Specific Gravity	1.38 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackffiller; Paint Scraper; Stepladder.

GUARANTEE

Medal Paints will guarantee this product for a period of 10 years subject to the adherence by the purchaser to comply with the “Instructions for Use “appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.