Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PROFESSIONAL TRADE BONDING LIQUID (SB)	No	PTBLS01
	Date	06/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Prof Trade Bonding Liquid is a solvent-based primer and sealer, which has been specially formulated to provide good penetrating properties for adhesion to very porous surfaces.
It can also be used to bind Powdery/Chalked Pva or Lime Wash to the original surface.

PRODUCT USES

- Suitable for sealing very porous surfaces such as Asbestos/Fibre Cement and Gypsum Plaster.
- Binding Powdery/Chalked Pva or Lime Washed surfaces.

PRODUCT BENEFITS

- Primer & Sealer
- Good Binding Properties
- Ideal for Chalked Pva Surfaces
- Apply with Brush or Roller
- Interior & Exterior Use
- Lead Free

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before commencing work.
Asbestos/Fibre Cement: Apply one coat of Prof Trade Bonding Liquid, followed by two topcoats of paint in the desired finish and colour. Allow sufficient drying time between coats.
Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Prof Trade Bonding Liquid, followed by two topcoats of paint in the desired finish and colour

Previously Painted Surfaces: Surface/s in poor condition such as Powdery/Chalked Pva or Lime-Wash. Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply one coat of Prof Trade Bonding Liquid, followed by one coat of Prof Trade Universal Undercoat (if necessary) and two topcoats of paint in the desired finish.

APPLICATION

Stir the contents thoroughly before use This product should be applied without thinning. Apply this product with a paintbrush or (mohair) paint roller and allow overnight drying time before applying the final coat/s of paint. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE

Clear finish.

SPREADING RATE

This product will cover approximately 10-12m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Solvent-Based
Finish	Clear
Drying Time @ 25°C	Touch Dry: 4 Hours
	Hard Dry : 16 Hours
Viscosity	10 - 15 Sec FC4 Cup @ 25°C
Storage	Dry and Cool area
Pack Size	5Lt

PRECAUTIONS

- Do not apply if rain is imminent
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.