Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PROFESSIONAL TRADE FIRST COAT PLASTER PRIMER

No	PTFCP01
Date	06/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION
First Coat Water based Plaster Primer is an economy range paint, suitable for all interior and exterior surfaces. This product has good alkali resistant and hiding power properties.

PRODUCT RECOMENDED USES
- ❑ New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork
- ❑ Asbestos/Fibre Cement Fascias & Ceiling Boards.
- ❑ Interior & Exterior Walls.

PRODUCT BENEFITS
- ❑ Quick Drying
- ❑ Alkali Resistant
- ❑ Apply with Brush or Lambswool Roller
- ❑ Interior & Exterior Use
- ❑ Lead Free

SURFACE PREPARATION
New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of First Coat Water based Plaster Primer followed by two topcoats in the desired finish.

Asbestos/Fibre Cement: Apply one coat of First Coat Water based Plaster Primer followed by two topcoats in the desired finish.

*** Not Recommended for Gypsum Plaster (Rhinolite):**

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply one coat of First coat Water based Plaster Primer followed by two topcoats in the desired finish.

APPLICATION
Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE
Available in white

SPREADING RATE
This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min to 1 Hour Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	112 -120 Krebs units
Specific Gravity	1.35 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS
- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature of 5 to 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Water immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST
Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackffiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE
This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.