

Product Data Sheet



Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PROF TRADE ROOF AND PAVING

No PTRP01

Date 04/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Professional Trade Roof & Paving Paint is a quality paint that provides exterior durability combined with excellent alkali resistance. This product will provide complete protection against harsh climatic conditions. It can be applied to Asbestos/Fibre Cement Tiles or Roof Sheets, Clay or Cement Roof Tiles and pre-primed Galvanised Iron Roofs.

PRODUCT USES

- Suitable for most types of Roofs & Paving.
- Concrete Window Sills.
- Asbestos/Fibre Cement tiles & Roof Sheets
- Pre-primed Metal & Wooden Surfaces
- Garden Pots

PRODUCT BENEFITS

- Excellent UV Resistance
- Good Durability
- All-Weather Finish
- Excellent Hiding Power
- Lead Free

SURFACE PREPARATION

New Surfaces: Thoroughly clean and prepare surface/s to be painted and use the correct primer prior to applying two (2) coats of Medal Professional Trade Roof & Paving Paint.

Galvanised Iron: Clean and remove all grease with Galvanised Iron Cleaner and rinse off with water before applying one (1) coat of Medal Dual Steel Primer, followed by two (2) coats of Medal Professional Trade Roof & Paving Paint.

Asbestos/Cement Roof Tiles and Floors: Thin the first (1) coat with 10% Water (Prime coat) followed by two (2) coats of Medal Professional Trade Roof & Paving Paint un-thinned.

Previously Painted Surfaces: Thoroughly clean and prepare surface/s by removing all dirt, grime, grease and flaking paint before painting. Powdery surfaces must be treated with one (1) coat of Medal Professional Trade Plasterbond, before applying two (2) coats of Medal Professional Trade Roof & Paving Paint.

APPLICATION

Stir the contents thoroughly before use. This product can be thinned down by 10% water to be used as a (Prime Coat). For colour consistency, ensure that batch numbers are the same on colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a block brush or

(Furpile/Lambswool) paint roller and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in standard colours.

SPREADING RATE

This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic
Finish	Semi Sheen
Drying Time @ 25°C	Touch Dry: 1 hour Hard Dry: 4 Hours
Re-coating Time	4 Hours
Viscosity	110 - 120 Kus
Specific Gravity	1.20 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt: 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- For best results paint between 08h00 –12h00 and 15h00 – 17h00.
- Keep out of reach of children.
- Wash hands with water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary
- Not recommended for Slate & Nutec tiles.**
- Not recommended for Driveways, Garage Floors and High Traffic Environments.**

TOOL CHECKLIST

Block Brush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack Filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of **seven** years provided a maintenance coat is applied every 24 months, subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

