Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL PROFESSIONAL TRADE WOOD VARNISH

No	PTWVA01
Date	06/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION
Prof Trade Wood Varnish is a good quality product suitable for Interior and Exterior wooden surfaces. A durable varnish that can be applied to a variety of surfaces such as wooden Doors, Window Frames, Skirting Boards, Furniture and more.

PRODUCT USES
- ❑ Surfaces made from Pine or Meranti.
- ❑ Wooden Fascias & Knotty Pine Ceilings.
- ❑ Cupboards and Furniture made from wood.

PRODUCT BENEFITS
- ❑ Durable Glossy Finish
- ❑ Fully Washable
- ❑ Hard-Wearing
- ❑ Apply with Brush
- ❑ Interior & Exterior Use
- ❑ Lead Free

SURFACE PREPARATION
New Surfaces: Thoroughly clean and prepare surfaces to be varnished. Sand to a smooth finish (in direction of grain) before varnishing. Apply the first coat thinned with 10%Mineral Turpentine, and another two (2) coats of Prof Trade Wood Varnish un-thinned. Apply by paint brush in the direction of the wood grain. For a glass-smooth finish, use Medal Sanding Sealer prior to applying this product.

Previously Varnished or Painted Surfaces: Thoroughly clean and prepare surfaces by removing all dirt, grime, grease and flaking varnish before varnishing. Sand to a smooth finish (in direction of grain) and apply two (2) coats of Prof Trade Wood Varnish. Previously painted surfaces finished with enamel-based paints must be stripped with a paint remover. Clean with water and allow to dry. Sand to a smooth finish (in direction of grain) and apply two (2) coats of Prof Trade Wood Varnish.

Warning: This product is not suitable for use on Wooden Floors, Gumpoles or Timber Fencing.

APPLICATION
Stir the contents thoroughly before use. This product should be applied without thinning. If thinning is required use Mineral Turpentine. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush and allow overnight drying time between coats. Clean tools (paintbrushes) with Mineral Turpentine immediately after use.

COLOUR RANGE
Available in Clear, Light Oak, Dark Oak, Teak and Mahogany

SPREADING RATE
This product will cover approximately 8-10m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Alkyd
Finish	Gloss
Drying Time @ 25 C	Touch Dry: 4 Hours
	Hard Dry : 16 Hours
Re-coating Time	16 Hours
Viscosity	55-60 Krebs Units
Specific Gravity	0.90 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS
- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature of 5 to 35C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Mineral Turpentine immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST
Paint Brush, Wood Filler, Sandpaper, Paint Scraper, Woodfiller; Mineral Turpentine, Mutton Cloth, Masking Tape, Dropsheet; Stepladder.

QUALITY GUARANTEE
This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.