Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL ROAD MARKING PAINT	No	MRMP01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Road Marking Paint is a quick drying alkyd-based paint suitable for new and previously painted bitumen and concrete roads, runways and parking lot surfaces. It is a durable product with excellent adhesion and re-coating capabilities.

PRODUCT USES

- Bitumen & Concrete Road surfaces.
- Sign writing of Roads.
- Marking of Parking areas.

PRODUCT BENEFITS

- Quick-drying
- Good Durability
- Excellent Hiding Power
- Apply with Brush, Roller or Spray
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

New & Previously Painted Surfaces: Surface/s must be thoroughly clean (free from gravel), dry and in sound condition before commencing work.
Apply one coat of Medal Road Marking Paint direct to the surface by laying-on an even coat of paint.

Warning: This product is not recommended for use on Swimming Pools or curing Damp problems.

APPLICATION

Stir the contents thoroughly before use For colour consistency, ensure that batch numbers are the same on all cans. For spray application thin down by up to 15% with Medal Road Marking Paint Reducer. Apply one coat with a paintbrush, paint roller or airless spray and allow 15 minutes to dry. Clean tools (brushes, rollers & spraying equipment) with Medal Road Marking Paint Reducer (thinners) immediately after use.

COLOUR RANGE

Available in standard colours namely White, Yellow, Black and Red.

SPREADING RATE

This product will cover approximately 5m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Alkyd
Finish	Matt
Drying Time @ 25°C	Touch Dry: 1-3 Minutes
	No Pick-up time: 15 Minutes
	Hard Dry : 45 Minutes
Viscosity	80 – 85 kus
Resistance to Sagging	Less than 1.75mm @ 375 micron wet film
Storage	Dry and Cool area
Pack Size	5Lt; 25Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Thinners and Hot Soapy Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- Wear protective clothing.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.