Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL SCHOOL BOARD PAINT	No	MSCB01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION
Medal School Board Paint is an excellent quality water-based paint that has been specially formulated for schools. This product has excellent abrasion resistance for long-term durability.

PRODUCT USES
- ❑ A Long-lasting paint finish for School Boards.

PRODUCT BENEFITS
- ❑ Durable Matt Finish
- ❑ Excellent Abrasion Resistance
- ❑ Apply with Brush or Roller
- ❑ Interior Use
- ❑ Lead free
- ❑ Quality Guaranteed

SURFACE PREPARATION
New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.
Cement Plaster, Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal School Board Paint.
Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat two coats of Medal School Board Paint.
Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal School Board Paint.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Sand lightly and apply two coats of Medal School Board Paint. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal School Board Paint.

APPLICATION
Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (short nap) paint roller and allow overnight drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE
Available in Matt Black & Green.

SPREADING RATE
This product will cover approximately 7-9m² /litre, depending on surface porosity.

TECHNICAL DATA
Type	Acrylic
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Minutes
	Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	100-110 Krebs Unit
Specific Gravity	1.30 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS
- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature of 5 to 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Water immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST
Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE
This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.