Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL STOEP PAINT	No	MSTP01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Stoep Paint is a good quality alkali-resistant enamel-based paint, which is primarily used to protect and decorate concrete floors and windowsills. This product is easy to apply and dries to a durable long-lasting gloss finish.

PRODUCT USES

- ❑ Suitable for Concrete, Cement Floors and Windowsills.
- ❑ Ideal for interior and exterior surfaces as specified above.

PRODUCT BENEFITS

- ❑ Hardwearing
- ❑ Alkali Resistant
- ❑ Fully Washable
- ❑ Easy to Clean & Maintain
- ❑ Interior & Exterior Use
- ❑ Lead Free
- ❑ Quality Guaranteed

SURFACE PREPARATION

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

New Surfaces: Surfaces must be thoroughly clean, dry and in sound condition and free from polish or wax before painting. Newly laid concrete floors must be allowed to dry for 6 weeks. Smooth floors must be cleaned with a mixture of hydrochloric acid and water (4parts water to 1part acid) and rinsed off with water and allowed to dry overnight before paint. Apply one coat of Medal Stoep Paint thinned with 10% Medal Mineral Turpentine, followed by two coats of Medal Stoep Paint un-thinned.

For slip resistance, add silica sand to the final coat.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, wax, polish and flaking paint before commencing to paint. Rub down with sandpaper and ensure surface is dry and clean and in sound condition before applying two coats of Medal Stoep Paint. Where powdery surfaces are evident, use one coat of Medal Bonding Liquid and allow to dry for a period of 16 hours prior to overcoating with two coats of Medal Stoep Paint.

For slip resistance, add silica sand to the final coat.

Warning: This product is not suitable for surfaces continually exposed to Oil / Grease or strong Solvents etc.

Silica sand additive must be added in the final coat to aid in non-slip properties.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller and allow 16 hours (overnight) drying time between coats. Allow the paint to cure for 7 days before attempting to clean the surface. For best results apply two coats of Medal Stoep Paint. Clean tools (brushes & rollers) with Medal Mineral Turpentine immediately after use.

COLOUR RANGE

Available in standard colours

SPREADING RATE

This product will cover approximately 8-10m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	Touch Dry: 4 hours
	Hard Dry : 16 Hours
Re-coating Time	16 Hours
Viscosity	80-85 Krebs units
Specific Gravity	1.10 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt,5Lt

PRECAUTIONS

- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature lower than 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with hot soapy water immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.