Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL WOOD VARNISH	No	MVAR01
	Date	05/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Wood Varnish is a superior quality product suitable for decorating and protecting all interior and exterior wooden surfaces. A durable varnish with excellent UV resistance, which can be applied to a variety of timber surfaces where a long-lasting glossy finish is required.

PRODUCT USES

- Internal and External Wooden Surfaces made from Pine or Meranti.
- Wooden Fascias & Knotty Pine Paneling and Ceilings.
- Cupboards made from Wood.
- Wooden Doors, Window Frames, Skirting Boards and Indoor/Outdoor Furniture.

PRODUCT BENEFITS

- All-Weather Protection
- Durable Glossy Finish
- Fully Washable
- Hard-Wearing
- Apply with Paintbrush
- Interior & Exterior Use
- Lead free
- 5 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before varnishing.
Sand surface (in the direction of the wood grain) to a smooth finish, and remove dust with a cloth. Apply one coat of Medal Sanding Sealer (if applicable), followed by two coats of Medal Wood Varnish. Allow overnight drying between coats. For best results, sand lightly between coats in the direction of the wood grain.

Previously Varnished or Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint or varnish. Sand lightly to a smooth finish. Apply two coats of Medal Wood Varnish, and allow overnight drying between coats. For best results, sand lightly between coats in the direction of the wood grain. Painted surfaces must be stripped back to bare wood than follow the "Instructions for Use" as described under New Surfaces.

Warning: This product is not suitable for use on Wooden Floors, Gumpoles or Timber Fencing.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush and allow overnight drying time between coats. Clean tools (paintbrushes) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in standard colours: Clear, Mahogany, Light Oak, Dark Oak and Teak.

SPREADING RATE

This product will cover approximately 8-10m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	Touch Dry: 4 Hours
	Hard Dry : 16 Hours
Re-coating Time	16 Hours
Viscosity	55- 60 Krebs Units
Specific Gravity	0.90 kg / litre
Storage	Dry and Cool area
Pack Size	500ml, 1Lt, 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paint Brush; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Woodfiller; Paint Scraper or Putty Knife; Stepladder.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of 5 years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.