Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL EVERBOND WATERPROOFING SEALANT

No	EBEBO01
Date	07/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Everbond is a non-toxic, fibre-reinforced flexible pure acrylic waterproofing system used in a wide variety of applications. It has extremely high UV resistance and excellent elongation properties, and it can take submersion under water for long periods of time. It can be applied to different surfaces to provide complete protection against the harshest weathering elements.

PRODUCT USES

- Sealing Concrete Dams, Reservoirs and Fishponds.
- Waterproofing Roofs, Walls and Parapet walls
- Salt Mist protection.

PRODUCT BENEFITS

- Non-Toxic (water-based)
- Membrane-Free System.
- Excellent UV Resistance
- Over-Coat with Water-Based Paints
- Apply with Brush, Roller or Spray
- Lead Free
- Quality Guaranteed

PREPARATION FOR DIFFERENT SURFACES

For more specific information related to correct application methods used for the different substrates, please refer to the relevant data specification sheets as described hereunder:

- **SP01: Asbestos Roofs**
- **SP02: Balconies**
- **SP03: Concrete Roofs**
- **SP04: Damp Substrates**
- **SP05: Expansion Joints**
- **SP06: Gutters**
- **SP07: IBR & Corrugated Roofs**
- **SP08: Parapet Walls & Hairline Cracks**
- **SP09: Showers**
- **SP10: Tiled Roofs**
- **SP11: Water Retainers**

The above-mentioned data specification sheets are available on request from Medal Paints.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush, paint roller or spray, and allow 2 to 6 hours drying time between coats. Clean tools (paintbrushes/equipment) with Water immediately after use.

COLOUR RANGE

Available in grey and standard colours.

SPREADING RATE

This product will cover approximately 1 litre /m², depending on film thickness applied. Based on SABS test method.

TECHNICAL DATA

Type	Pure Acrylic
Finish	Semi-Sheen
Drying Time @ 25°C	Touch Dry: 30 Min to 1 Hour
	Hard Dry : 48-72 Hours
Re-coating Time	2 – 6 Hours
Tensile Strength	2 Mpa
Flexibility	100%
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- This product is not suitable for Swimming Pools.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.