Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL SAFARI ACRYLIC PVA	No	SFPVA01
	Date	07/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Safari Acrylic Pva is an economical smooth Matt water-based paint suitable for interior & exterior walls and ceilings. This product can be used to a variety of different surfaces.

PRODUCT USES

- ❑ Cement Plastered Walls.
- ❑ Asbestos/Fibre Cement Ceiling Boards.
- ❑ Suitable for Garage and Storeroom Walls.
- ❑ Low-Cost Housing.

PRODUCT BENEFITS

- ❑ Smooth Matt Finish
- ❑ High Hiding
- ❑ Apply with Brush or Roller
- ❑ Interior & Exterior Use
- ❑ Lead Free

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Safari Acrylic Pva. For low-cost applications, apply two coats of Safari Acrylic Pva direct to the surface.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Bond, followed by two coats of Safari Acrylic Pva.

Iron & Steel: Apply one coat of Medal Dual Steel Primer followed by one coat of Medal Universal Undercoat and two coats of Safari Acrylic Pva.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Safari Acrylic Pva.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply two coats of Safari Acrylic Pva direct to the surface. Powdery surfaces must be treated with one coat of Medal Plaster Bond prior to applying two coats of Safari Acrylic Pva. Note: Enamel based surfaces to be painted with an Acrylic Pva must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Safari Acrylic Pva.

Warning: This product is specifically made for low-cost applications and should not be used as a finish coat for normal domestic or commercial use. A better-quality Medal Acrylic Pva is highly recommended to provide long-term durability and complete protection against the weathering elements.

Warning: This product is specifically made for low-cost applications and should not be used as a finish coat for normal domestic or commercial use. A better-quality Medal Acrylic Pva is highly recommended to provide long-term durability and complete protection against the weathering elements.

Note: This product should be applied un-thinned, as adding water will affect the overall performance of this paint.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white and standard colours.

SPREADING RATE

This product will cover approximately 4-6m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 1 Hour
Re-coating Time	4 Hours
Viscosity	100 – 120 KUs
Specific Gravity	1.32 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- ❑ Do not apply if rain is imminent.
- ❑ Apply at an ambient temperature of 5 to 35°C.
- ❑ Keep out of reach of children.
- ❑ Wash hands with Water immediately after use.
- ❑ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paint Brush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Stepladder.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.