Product Data Sheet

Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL SAFARI GLOSS ENAMEL	No	SFGEN01
	Date	07/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Safari Gloss Enamel is an economy range paint suitable for Interior and Exterior surfaces. A durable product that can be applied to a variety of new or previously painted surfaces such as Cement Plaster; Asbestos/Fibre Cement Wood and Steelwork.

PRODUCT USES

- New and previously painted surfaces made from Cement Plaster.
- Primed Metal & Wooden Surfaces.
- Ideal for Steel Door & Window Frames; Interior Walls; Kitchen & Bathroom Walls; Gates; Steel Fencing etc.

PRODUCT BENEFITS

- Glossy Finish
- Fully Washable
- Apply with Brush or Roller
- Interior & Exterior Use
- Lead Free

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer followed by two coats Safari Gloss Enamel.

Galvanised Iron: Remove all oil/grease from surface before painting, apply one coat of Meda QD Red Oxide Primer, followed by two coats of Safari Gloss Enamel.

Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Solvent Etch Primer followed by one coat of Medal Universal Undercoat, and two coats of Safari Gloss Enamel.

Timber/Wood: Lightly sand surface to a smooth finish before painting. Apply one coat of Medal Pink Wood Primer, followed by two coats of Safary Gloss Enamel.

Gypsum Plaster: Apply one coat Medal Plaster Primer before applying two coats of Safari Gloss Enamel.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Spot prime all bare areas with the correct primer, followed be one coat of Medal Universal Undercoat (if applicable) and two coats of Safari Gloss Enamel.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in white and standard colours.

SPREADING RATE

This product will cover approximately 4 - 6m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Universal Alkyd
Finish	Gloss
Drying Time @ 25°C	Touch Dry: 4 Hours
	Hard Dry : 16 Hours
Re-coating Time	16 Hours
Viscosity	80-85 Krebs units
Specific Gravity	1.10 kg / litre
Storage	Dry and Cool area
Pack Size	500ml;1Lt; 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water immediately and consult a physician if necessary.

TOOL CHECKLIST

Paint Brush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Stepladder.

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.