

# Product Data Sheet



## Steel Cladd All in One

No SCAIO02

Date 04/26

Steel Cladd products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Steel Cladd All in One is a high quality pure acrylic based primer and topcoat in one suitable for all interior and exterior Iron and Steel surfaces. This product has excellent adhesion, water resistance and hiding power properties.

### PRODUCT RECOMMENDED USES

- New and previously painted Iron and steel surfaces
- Interior and Exterior Use.

### PRODUCT BENEFITS

- Quick Drying
- Low Odour
- Excellent Adhesion and Intercoat Adhesion
- Apply with Brush or Furple Roller
- Quality Guaranteed

### SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

**Iron and Steel:** Thoroughly clean and prepare surface by removing all dirt, rust, grease, and grime before painting. Lightly sand and clean then apply two coats of Steel Cladd All in One.

**Previously Painted Surfaces:** Thoroughly clean and prepare surface by removing all dirt, rust, grease, and grime before painting. Sand to bare surface and apply two coats of Steel Cladd All in One.

### APPLICATION

Stir the contents thoroughly before use. This product should be applied **WITHOUT THINNING**. For consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furple) paint roller and allow +/- 4 - 6 hours drying time between coats. Allow paint to cure for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

**“NOT RECOMMENDED for Roof, Bath and Showers, Floors, Kitchen area and Damp conditions”**

**Please Note: Do not use a spray application**

### COLOUR RANGE

Available in White, Black, Brown, Charcoal, Grey, Green, Red

### SPREADING RATE

This product will cover approximately 6-8 m<sup>2</sup> /litre, depending on surface porosity.

### TECHNICAL DATA

<b>Type</b>	Acrylic Based Pva
<b>Finish</b>	Semi - Sheen
<b>Drying Time @ 25°C</b>	Touch Dry: 2 Hours Hard Dry : 4 - 6 Hours
<b>Re-coating Time</b>	4 - 6 Hours
<b>Viscosity</b>	100 -120 Krebs Units
<b>Storage</b>	Dry and Cool area
<b>Pack Size</b>	1Lt, 5Lt and 20Lt

### PRECAUTIONS

Do not apply if rain is imminent.  
Apply at an ambient temperature of 5 to 35°C.  
Keep out of reach of children.  
Wash hands with Water immediately after use.  
Skin or Eye contact: clean with fresh water and consult a physician if necessary.

### TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

### QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

