

# Product Data Sheet



Medal Paints (Pty) Limited  
Cnr Main Reef Rd & Kelvin St  
Industria, Johannesburg.  
PO Box 1471  
Crown Mines  
2025.  
Tel: +27 11 661 5700

## MEDAL EVERSEAL FLEXIBLE WATERPROOFING

No EBESE01

Date 09/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Everseal is a high-quality acrylic waterproofing used in conjunction with a membrane, which has been especially formulated to seal and protect all exterior surfaces. A highly flexible product with excellent elongation and UV resistant properties, which can be applied to a variety of surfaces where a "water-tight" system is required.

### PRODUCT USES

- Waterproofing Roofs, Walls and Parapet Walls.
- Flashings, Roof Valleys, Overlapping Roof Sheets.
- Roof Screws and Weather Walls.
- Ideal for Galvanised Iron and Tiled roofs.

### PRODUCT BENEFITS

- Non-Toxic (water-based)
- Provides Complete Protection
- Excellent UV Resistance
- Over-Coat with Water-Based Paints
- Apply with a Paintbrush/Lambswool Roller
- Quality Guaranteed
- Lead Free

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before commencing to waterproof.

**Roofs, Parapets & Flashings:** Apply one thick basecoat to the surface. Place membrane firmly onto the basecoat and apply another coat while the treated surface area is still wet. Allow sufficient time to dry before applying the final coat of Everseal. Apply two coats of a good quality Roof Paint (if necessary).

**Cement Plastered Walls:** Apply one thick basecoat to the surface. Place membrane firmly onto the basecoat and apply another coat while the treated surface area is still wet. Allow sufficient time to dry before applying one to two finish coats of a good quality exterior Acrylic Pva (if necessary).

**Previously Painted/Waterproofed Surfaces:** Thoroughly clean and prepare surface/s by removing all dirt, grease, grime, surface rust, old waterproofing and flaking paint. Apply this product as described under New Surfaces. Powdery surfaces must be sealed with one coat of Everprime Bonding Liquid, prior to using this product.

### APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or lambswool roller, and allow 4 to 6 hours drying time

between coats. Clean tools (paintbrushes etc.) with Water immediately after use.

### COLOUR RANGE

Available in white and standard colours.

### SPREADING RATE

This product will cover approximately 2 litres / m<sup>2</sup>, based on a 3-coat application and film thickness applied.

### TECHNICAL DATA

Type	Water based Acrylic
Finish	Semi-Sheen
Drying Time @ 25°C	Touch Dry: 30 Min to 1 Hour Hard Dry : 48-72 Hours
Re-coating Time	4-6 Hours
Viscosity	95 – 108 Krebs Units
Specific Gravity	1.20
Flexibility	100%
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

### PRECAUTIONS

- Do not apply if rain is imminent or on surfaces with long-term ponding.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- This product is **NOT** suitable for Swimming Pools.
- 

### GUARANTEE

This product is marketed by Medal Paints under the Everseal brand name, which is guaranteed for a period of up to five years and subject to:

1. The affected surface/s are maintained every 2 years with two coats of Everseal
2. The "Instructions for Use" listed under the relevant Data Specification sheets have been correctly followed by the end user.

**Warning:** Ensure that the membrane is completely saturated with waterproofing liquid and applied correctly without creasing or entrapped air. Do not apply if rain is imminent or on surfaces with long-term ponding.