

# Product Data Sheet



Medal Paints (Pty) Limited  
Cnr Main Reef Rd & Kelvin St  
Industria, Johannesburg.  
PO Box 1471  
Crown Mines  
2025.  
Tel: +27 11 661 5700

## MEDAL PREMIUM ALL IN ONE QUICK DRYING WOOD VARNISH

No MQDWW01

Date 09/25

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Medal Premium Solvent-based All in One Quick Drying Wood Varnish is an UV resistant, self-priming, preservative topcoat. The vibrant colour shades revitalize imperfect wood with an exceptional direct to wood glossy finish.

A durable varnish formulated to protect and beautify interior and exterior wooden surfaces, such as Doors, Window Frames, Skirting Boards, Furniture and more.

### PRODUCT USES

- Surfaces made from Pine or Meranti.
- Wooden Fascias & Knotty Pine Ceilings.
- Cupboards and Furniture made from wood.

### PRODUCT BENEFITS

- Durable Glossy Finish
- Fully Washable
- Hard-Wearing
- Quick Drying
- Interior & Exterior Use
- UV Resistant
- Wood Preservative
- Knotting Sealer
- Sanding Sealer
- Apply with Brush and Spray
- Lead Free
- 10 Year Guarantee

### SURFACE PREPARATION

**New Surfaces:** Thoroughly clean and prepare surfaces to be varnished. Sand to a smooth finish (in direction of grain) before application. Apply the first penetration coat and allow to dry for 4 hours and another two (2) coats of Medal Premium All in One Quick Drying Wood Varnish maintaining a drying time of 4 hours in-between coats. Apply with paint brush or spray in the direction of the wood grain.

**Previously Varnished or Painted Surfaces:** Thoroughly clean and prepare surfaces by removing all dirt, grime, grease and flaking varnish before application. Sand to a smooth finish (in direction of grain) and apply two (2-3) coats Medal Premium All in One Quick Drying Wood Varnish. Previously painted surfaces finished with enamel-based paints must be sanded to the bare substrate. Apply two (2-3) coats of Medal Premium All in One Quick Drying Wood Varnish maintaining 4 hours drying time between coats.

### APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush, or spray gun and allow 4 hours drying time in-between coats. Clean tools (paintbrushes) with Medal QD Thinners immediately after use.

### COLOUR RANGE

Available in Clear, Light Oak, Dark Oak, Teak, Mahogany and Ebony.

### SPREADING RATE

This product will cover approximately 8-10m<sup>2</sup> /litre, depending on surface porosity.

### TECHNICAL DATA

|                              |                      |
|------------------------------|----------------------|
| Type:                        | Alkyd                |
| Finish:                      | Glossy               |
| Viscosity                    | 85-95 seconds F4 Cup |
| Specific Gravity             | 0.94 kg / litre      |
| Drying Time @ 25 C Touch Dry | 1 Hour               |
| Hard Dry:                    | 4 Hours              |
| Re-coating Time:             | 4 Hours              |
| Storage:                     | Dry and Cool area    |
| Pack Size:                   | 1Lt; 5Lt; 20Lt       |

### PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35C.
- Keep out of reach of children.
- Wash hands with Medal QD Thinners and warm water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

### TOOL CHECKLIST

Paint Brush, Wood Filler, Sandpaper, Paint Scraper, Medal QD Thinners, Mutton Cloth, Masking Tape, Drop sheet, Stepladder.

### QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of 10 years on condition a maintenance coat every 2 years is applied, subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

