

Product Data Sheet



Medal Paints (Pty) Limited
Cnr Main Reef Rd & Kelvin St
Industria, Johannesburg.
PO Box 1471
Crown Mines
2025.
Tel: +27 11 661 5700

MEDAL EVERLOCK Pebble Bond

No	EBLCK01
Date	07/26

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Everlock Pebble Bond is an easy-to-use, water-based adhesive binder designed to securely hold decorative stones, bark, mulch, pebbles, and more in place, preventing them from shifting or becoming untidy in your landscaping projects. What makes Medal Everlock Pebble Bond so popular in landscaping is its simplicity and ease of use, offering a hassle-free solution compared to other binding systems. Medal Everlock Pebble Bond binds the materials together securely, creating a natural-looking finish while ensuring the aggregates stay firmly in place. As the product dries, it forms strong bonds between the materials, resulting in a neat, long-lasting finish with minimal effort.

PRODUCT USES

- Decorative Garden Paths
- Flower Beds & Borders
- Around Outdoor Lighting
- Rock Gardens
- Landscape Edging
- Mulch Around Trees & Shrubs
- Outdoor Living Spaces

PRODUCT BENEFITS

- ☐ Easy and Simple Application
- ☐ Water-Based Formula
- ☐ Plant Safe
- ☐ Non-Toxic and Pet Safe
- ☐ Air Drying
- ☐ Multi-Purpose Usage
- ☐ Strong, Long-Lasting Adhesive Bond
- ☐ Weather-Resistant (once dried)
- ☐ Natural Finish Appearance
- ☐ Hassle Free Application
- ☐ Lead Free

Note: Not suitable for heavy traffic areas

APPLICATION

• Spray Application (Recommended for smaller areas)

1. Place the stones or mulch evenly.
2. Using a low-pressure garden sprayer, apply Medal Everlock Pebble Bond evenly over the entire surface.
3. Continue spraying until the surface is thoroughly wetted without excessive pooling.
4. Allow the binder to penetrate between the stone.
5. Allow 24 hours for 1st coat to dry before applying additional coats.

• Mix Before Laying

1. Pour the required quantity of stones or gravel into a mixing bucket or wheelbarrow.
2. Add Medal Everlock Pebble Bond gradually while mixing until all stone are evenly coated.
3. Spread the coated aggregate onto the prepared area.
4. Level and lightly compact if required.

• Pouring (Recommended for larger areas as this method ensures full coverage and better control)

1. Pour Medal Everlock Pebble Bond into a watering can, give it a quick stir.
2. Apply evenly across the prepared area.
3. Level and lightly compact if required.
4. Allow 24 hours for the 1st coat to dry before applying additional coats.

Do Not Apply

- During rain
- On wet substrates
- If rain expected within 24 hours
- On muddy or contaminated surfaces

COLOUR RANGE

Dries to a natural clear finish

SPREADING RATE

This product will cover approximately 2 m²/litre, depending on surface porosity.

*** Please note that coverage may vary depending on the stone size and the application method used (higher saturation results in less coverage).**

TECHNICAL DATA

Type	Pure Acrylic
Finish	Sheen
Drying Time @ 25°C	Touch Dry: 4 Hour Hard Dry : 16 Hours
Re-coating Time	24 Hours
Specific Gravity	1.04 kg / litre
Storage	Dry and Cool area
Pack Size	2.5Lt; 5Lt

PRECAUTIONS

- ☐ Do not apply if rain is imminent.
- ☐ Apply at an ambient temperature of 5 to 35°C.
- ☐ Keep out of reach of children.
- ☐ Wash hands with water immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- ☐ Wear protective clothing such as Overall, Gloves; Goggles etc

Warning: Additionally, for maintenance, jet washing or high-pressure washing should be avoided, as this may damage the bond and surface.

Gentle cleaning methods are recommended to preserve the integrity of the adhesive and the surface over time.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer. 1 year guarantee with a maintenance coat once a year.

*****Recommendation for surface preparation*****

*****Please read the information on the back of packaging*****

The information given in this Product Data Sheet OR Safety Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Medal Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Medal products. Paint technology is continuously being developed, and Medal Paints reserves the right to update product specifications without prior notice. Contact Medal Paints for further details on 0860 063 325.